

1		2		3		4	
This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission							
REV		DESCRIPTION OF REVISION		ECN NO.		BY	
A		Initial Release		---		T. Haiyun	
DATE		17/3/13		DATE		17/3/13	
APPROVED		17/3/13		APPROVED		17/3/13	

1 Electrical

1.1 Impedence 50 Ω

1.2 Insulation resistance: ≥10000M Ω

1.3 Frequency DC-6G

1.4 VSWR ≤ 1.3

1.5 Insertion Loss ≤ 0.4dB

1.6 Rated Power 200W

1.7 Initial Discharge Voltage 230V

1.8 Peak Discharge Current 10KA

2 Environmental

2.1 Temperature range -45℃~85℃

2.2 RoHs Compliant

3 Materials&Finish

3.1 Body: Brass, Nickel plated

3.2 Insulator: Teflon

3.3 Contact Pin: Bronze, gold plated

3.4 Gasket: Silicon rubber (red color)

5/8-24UNEF-2A

61, 5

5/8-24UNEF-2A

SW14

0 H S

✓

TRL

www.terulai.com

N Female to Female Bulkhead Surge Arrestor

Part No: TRL-BLQ-347931

DRAWN: T. Haiyun 17/3/13

ENGINEER: C. Tao 17/3/13

APPROVED: W. Qiang 17/3/13

TOLERANCES UNLESS OTHERWISE SPECIFIED

X ±0.50

.X ±0.20

.XX ±0.10

ANGLES ±1°

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME

2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

1

2

3

4