

1	2	3	4
This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission			
1 Electrical		A	
1.1 Impedence	50 Ω		
1.2 Insulation resistance:	≥100000MΩ		
1.3 Frequency	DC-3G		
1.4 VSWR	≤ 1.25		
1.5 Insertion Loss	≤ 0.4dB		
1.6 Rated Power	200W		
1.7 Initial Discharge Voltage	230V		
1.8 Peak Discharge Current	10KA		
2 Environmental		B	
2.1 Temperature range	-45℃~85℃		
2.2 RoHs Compliant			
3 Materials&Finish			
3.1 Body:	Brass, Nickel plated		
3.2 Insulator:	Teflon		
3.3 Contact Pin:	Branze, gold plated		
3.4 Coupling Nut:	Brass, Nickel plated		
3.5 Gasket:	Silicon rubber (red color)		
3.6 C-ring:	Phosphor bronze, nickel plated		
A		B	
22		(68.4)	
5/8-24UNEF-2A			
R 0 H S			
TITLE: N-JKYP		www.t-rely.com.cn	
N male to Female Bulkhead Surge Arrestor		DIMENSION IN MILLIMETERS (mm)	
PART NO: TRL-BUQ-347930		SCALE: N/A	
DRAWN: T. Haiyun 17/3/13		SIZE: A4	
ENGINEER: C. Tao 17/3/13		SHEET: 1/1	
APPROVED: W. Qiang 17/3/13		REV: A	
TOLERANCES UNLESS OTHERWISE SPECIFIED			
X +0.50			
.X +0.20			
.XX +0.10			
ANGLES ±°			
NOTES:			
1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME			
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY			
1		4	